

Radiation Sensor BG51

- Nuclear Beta and Gamma Radiation Sensor
- Ultra Low Power Requirement

Description

The function of the BG51 radiation sensor is based on an array of customized PIN diodes. The integrated pulse discriminator with a temperature compensated threshold level provides true TTL signal output. The BG51 is capable of detecting beta radiation (electrons), gamma radiation (photons) and X-rays.

The performance of the BG51 solid state sensor, in combination with high immunity to electrostatic fields make it a good choice for new state-of-the-art designs as well as for upgrading existing designs.

Features and Benefits

- Detects beta and gamma radiation and X-rays
- Ultra low power requirement (25µA)
- Pulse Rate vs. Radiation Rate: 300 cph/µSv/h
- High immunity to RF and electrostatic fields
- Linear response over wide temperature range (-30°C to 60°C)
- Swiss made

Applications

- Equipment for detecting radioactivity in medical environment
- Radiation monitors for nuclear safeguards and security
- Gamma detector to detect illicit nuclear material
- Education on nuclear physics
- CubeSats conducting scientific investigations in space

 Copyright © Teviso Sensor Technologies Ltd 2025

Absolute Maximum Ratings


Supply voltage, V_{CC} to GND	18.0V
Output short-circuit current	continuous
Storage temperature range	-65°C to 100°C

Electrical characteristics

Unless otherwise indicated specified at:
V_{CC} = 4.0V, T_A = 25°C


Measurement range of dose rate	0.1 µSv/h to 100 mSv/h
Pulse Rate vs. Radiation Rate	300 cph ± 15% for 1 µSv/h
Energy response	70 keV to 2 MeV
Output pulse level	Equal to supply voltage (positive going)
Output pulse width	50 µs to 200 µs (LOW→HIGH→LOW)
Supply voltage range, V_{CC}	2.5V to 10.0V
Supply current, I_S	25µA TYP
Operating temperature range	-30°C to 60°C

BG51 Sensor Linearity




dH*(10) / dt = Radiation dose equivalent rate for Cs-137 and Co-60 (mSv/h)


 Copyright © Teviso Sensor Technologies Ltd 2025




BG51 Directional Response
Front: 100%, Back: 45%



BG51 Functional Block Diagram



BG51 Outline Dimensions
(in millimeter)



BG51 Connection Descriptions

 Copyright © Teviso Sensor Technologies Ltd 2025

Application Information

BG51 / BG51-OEM foot print and mechanical specification

https://www.teviso.com/documents/bg51-mechanical-specification.pdf

Preventing false measurements

https://www.teviso.com/documents/how-to-prevent-false-measurements.pdf

Facts about radioactivity

https://www.teviso.com/documents/how-to-live-with-radioactivity.pdf

Disclaimer

Neither the whole nor any part of the information contained in, or the product described in this datasheet, may be adapted or reproduced in any material or electronic form without the prior written consent of the copyright holder.

This product and its documentation are supplied on an as is basis and no warranty as to their suitability for any particular purpose is either made or implied. Teviso Sensor Technologies will not accept any claim for damages howsoever arising as a result of use or failure of this product. Your statutory rights are not affected.

This product or any variant of it is not intended for use in any medical appliance, device or system in which the failure of the product might reasonably be expected to result in personal injury.

This document provides preliminary information that may be subject to change without notice.